



NOTES:-

- 1) Made from 99.9% pure seamless copper tubes as per ASTM B188
- 2) UL 486 tested & approved
- 3) Meets SAE conductivity standards J163 and J1811
- 4) Flare barrel for easy cable entry
- 5) Electro tin plate-thickness 2 to 5 Micron
- 6) Rated for up to 600V D.C.
- 7) RoHS & REACH compliant

			REVISE ONLY ON CAD SYSTEM				
			TITLE				
			Tinned Copper Battery Cable Lugs				
			DRAWING NO.				
			MD0114P				
			PART NO. - MD0114P		SHEET NO. 1 OF 1		
REV NO.    DATE    SIGN 0        03-APL-2020    J.GAJJAR			DIMENSIONS SHOWN IN INCH UNLESS OTHERWISE SPECIFIED TOLERLANCES $\pm 10\%$		DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		
DRWG. MDD BY 03-APL-2020		CHK'D. JMG BY 03-APL-2020		FILE NAME		THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO SELTERM LLC,USA AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION.	
APP'D. AGP BY 03-APL-2020		SCALE NTS		DIV		SIZE A	