



NOTES:-

- 1) Made from 99.9% pure seamless copper tubes as per ASTM B188
- 2) UL 486 tested & approved
- 3) Meets SAE conductivity standards J163 and J1811
- 4) Flare barrel for easy cable entry
- 5) Electro tin plate-thickness 2 to 5 Micron
- 6) Rated for up to 600V D.C.
- 7) RoHS & REACH compliant

| | | | | | | |
|---|--|---|--|------------------|--|--|
| | | | REVISE ONLY ON CAD SYSTEM | | | |
| | | | TITLE | | | |
| | | | Tinned Copper Battery Cable Lugs | | | |
| | | | DRAWING NO. | | | |
| | | | MD0214P | | | |
| | | | PART NO. - MD0214P | | SHEET NO. 1 OF 1 | |
| REV NO. 0 DATE 03-APL-2020 SIGN J.GAJJAR | | | DIMENSIONS SHOWN IN INCH UNLESS OTHERWISE SPECIFIED TOLERLANCES $\pm 10\%$ DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS | | FILE NAME THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO SELTERM LLC,USA AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION. | |
| DRWG. MDD BY 03-APL-2020 APP'D. AGP BY 03-APL-2020 | | CHK'D. JMG BY 03-APL-2020 SCALE NTS | | DIV SIZE A | | |