


NOTES:-

- 1)Made from 99.9% pure seamless copper tubes as per ASTM B188
- 2)UL 486 tested & approved
- 3)Meets SAE conductivity standards J163 and J1811
- 4)Flare barrel for easy cable entry
- 5)Electro tin plate-thickness 2 to 5 Micron
- 6)Rated for up to 600V D.C.
- 7)RoHS & REACH compliant

| | | | | | | |
|---|--|--|---|--|---|--|
| | | | REVISE ONLY ON CAD SYSTEM | | | |
| | | | TITLE | | | |
| | | | Tinned Copper Battery Cable Lugs | | | |
| 0 03-APL-2020 J.GAJJAR REV NO. DATE SIGN | | | DIMENSIONS SHOWN IN INCH UNLESS OTHERWISE SPECIFIED TOLERLANCES ±10% | | DRAWING NO. | |
| DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS | | |  | | MD0238PW | |
| DRWG. MDD CHK'D. JMG BY 03-APL-2020 BY 03-APL-2020 APP'D. AGP SCALE BY 03-APL-2020 NTS | | | PART NO. - MD0238PW | | SHEET NO. 1 OF 1 | |
| | | | FILE NAME | | THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO SELTERM LLC,USA AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION. | |
| | | | | | DIV SIZE | |
| | | | | | A | |