



NOTES:-

- 1)Made from 99.9% pure seamless copper tubes as per ASTM B188
- 2)UL 486 tested & approved
- 3)Meets SAE conductivity standards J163 and J1811
- 4)Flare barrel for easy cable entry
- 5)Electro tin plate-thickness 2 to 5 Micron
- 6)Rated for up to 600V D.C.
- 7)RoHS & REACH compliant

REVISE ONLY ON CAD SYSTEM		
TITLE		
Tinned Copper Battery Cable Lugs		
DRAWING NO.		
MD0238P		
PART NO. - MD0238P		SHEET NO. 1 OF 1
REV NO.	DATE	SIGN
0	03-APL-2020	J.GAJJAR
DIMENSIONS SHOWN IN INCH UNLESS OTHERWISE SPECIFIED TOLERLANCES ±10%		
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		
DRWG.	MDD	CHK'D. JMG
BY 03-APL-2020		BY 03-APL-2020
APP'D. AGP		SCALE
BY 03-APL-2020		NTS
FILE NAME		DIV
THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO SELTERM LLC,USA AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION.		SIZE
		A