



NOTES:-

- 1) Made from 99.9% pure seamless copper tubes as per ASTM B188
- 2) UL 486 tested & approved
- 3) Meets SAE conductivity standards J163 and J1811
- 4) Flare barrel for easy cable entry
- 5) Electro tin plate-thickness 2 to 5 Micron
- 6) Rated for up to 600V D.C.
- 7) RoHS & REACH compliant

| | | | | | | |
|----------------|--|--|----------------------------------|--|--|--|
| | | | REVISE ONLY ON CAD SYSTEM | | | |
| | | | TITLE | | | |
| | | | Tinned Copper Battery Cable Lugs | | | |
| | | | DRAWING NO. | | | |
| | | | MD0238UW | | | |
| | | | PART NO. - MD0238UW | | SHEET NO. 1 OF 1 | |
| DRWG. MDD | | | CHK'D. JMG | | FILE NAME | |
| BY 03-APL-2020 | | | BY 03-APL-2020 | | THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO SELTERM LLC, USA AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION. | |
| APP'D. AGP | | | SCALE | | DIV | |
| BY 03-APL-2020 | | | NTS | | SIZE | |
| | | | | | A | |