



NOTES:-

- 1) Made from 99.9% pure seamless copper tubes as per ASTM B188
- 2) UL 486 tested & approved
- 3) Meets SAE conductivity standards J163 and J1811
- 4) Flare barrel for easy cable entry
- 5) Electro tin plate-thickness 2 to 5 Micron
- 6) Rated for up to 600V D.C.
- 7) RoHS & REACH compliant

			REVISE ONLY ON CAD SYSTEM			
			TITLE			
			Tinned Copper Battery Cable Lugs			
			DRAWING NO.			
			MD0438P			
			PART NO. - MD0438P		SHEET NO. 1 OF 1	
REV NO. DATE SIGN 0 03-APL-2020 J.GAJJAR			DIMENSIONS SHOWN IN INCH UNLESS OTHERWISE SPECIFIED TOLERANCES $\pm 10\%$ DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		FILE NAME THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO SELTERM LLC,USA AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION. DIV SIZE	
DRWG. MDD CHK'D. JMG BY 03-APL-2020 BY 03-APL-2020 APP'D. AGP SCALE NTS BY 03-APL-2020			THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO SELTERM LLC,USA AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION.		DIV SIZE A	

