



NOTES:-

- 1)Made from 99.9% pure seamless copper tubes as per ASTM B188
- 2)UL 486 tested & approved
- 3)Meets SAE conductivity standards J163 and J1811
- 4)Flare barrel for easy cable entry
- 5)Electro tin plate-thickness 2 to 5 Micron
- 6)Rated for up to 600V D.C.
- 7)RoHS & REACH compliant

			REVISE ONLY ON CAD SYSTEM			
			TITLE			
			Tinned Copper Battery Cable Lugs			
REV NO.			DATE		SIGN	
0			03-APL-2020		J.GAJJAR	
DIMENSIONS SHOWN IN INCH						
UNLESS OTHERWISE SPECIFIED						
TOLERLANCES $\pm 10\%$						
DRAFT WHERE APPLICABLE						
MUST REMAIN WITHIN						
DIMENSIONS						
DRWG. MDD			CHK'D. JMG			
BY 03-APL-2020			BY 03-APL-2020			
APP'D. AGP			SCALE			
BY 03-APL-2020			NTS			
PART NO. - MD0456PW			DRAWING NO.		SHEET NO.	
			MD0456PW		1 OF 1	
FILE NAME			THIS DRAWING CONTAINS INFORMATION THAT IS			DIV
			PROPRIETARY TO SELTERM LLC,USA AND SHOULD NOT BE			SIZE
			USED WITHOUT WRITTEN PERMISSION.			A