



NOTES:-

- 1) Made from 99.9% pure seamless copper tubes as per ASTM B188
- 2) UL 486 tested & approved
- 3) Meets SAE conductivity standards J163 and J1811
- 4) Flare barrel for easy cable entry
- 5) Electro tin plate-thickness 2 to 5 Micron
- 6) Rated for up to 600V D.C.
- 7) RoHS & REACH compliant

			REVISE ONLY ON CAD SYSTEM			
			TITLE			
			Tinned Copper Battery Cable Lugs			
			DRAWING NO.			
			MD0638PX			
			PART NO. - MD0638PX		SHEET NO. 1 OF 1	
REV NO. 0 DATE 03-APL-2020 SIGN J.GAJJAR			DIMENSIONS SHOWN IN INCH UNLESS OTHERWISE SPECIFIED TOLERLANCES $\pm 10\%$ DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		FILE NAME THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO SELTERM LLC,USA AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION.	
DRWG. MDD BY 03-APL-2020 APP'D. AGP BY 03-APL-2020			CHK'D. JMG BY 03-APL-2020 SCALE NTS		DIV SIZE A	