



NOTES:-

- 1)Made from 99.9% pure seamless copper tubes as per ASTM B188
- 2)UL 486 tested & approved
- 3)Meets SAE conductivity standards J163 and J1811
- 4)Flare barrel for easy cable entry
- 5)Electro tin plate-thickness 2 to 5 Micron
- 6)Rated for up to 600V D.C.
- 7)RoHS & REACH compliant

| | | | | | | |
|----------------------------|-------------|--------|----------------------------------|--|---|-------------|
| | | | REVISE ONLY ON CAD SYSTEM | | | |
| | | | TITLE | | | |
| | | | Tinned Copper Battery Cable Lugs | | | |
| 0 | | | 03-APL-2020 | | J.GAJJAR | |
| REV NO. | DATE | SIGN | | | | |
| DIMENSIONS SHOWN IN INCH | | | | | | |
| UNLESS OTHERWISE SPECIFIED | | | | | | |
| TOLERLANCES $\pm 10\%$ | | | | | | |
| DRAFT WHERE APPLICABLE | | | | | | |
| MUST REMAIN WITHIN | | | | | | |
| DIMENSIONS | | | | | | |
| DRWG. | MDD | CHK'D. | JMG | PART NO. - MD0812PX | | DRAWING NO. |
| BY | 03-APL-2020 | BY | 03-APL-2020 | | | MD0812PX |
| APP'D. | AGP | SCALE | NTS | SHEET NO. | | 1 OF 1 |
| BY | 03-APL-2020 | | | FILE NAME | THIS DRAWING CONTAINS INFORMATION THAT IS | DIV |
| | | | | PROPRIETARY TO SELTERM LLC,USA AND SHOULD NOT BE | | SIZE |
| | | | | USED WITHOUT WRITTEN PERMISSION. | | A |