



NOTES:-

- 1)Made from 99.9% pure seamless copper tubes as per ASTM B188
- 2)UL 486 tested & approved
- 3)Meets SAE conductivity standards J163 and J1811
- 4)Flare barrel for easy cable entry
- 5)Electro tin plate-thickness 2 to 5 Micron
- 6)Rated for up to 600V D.C.
- 7)RoHS & REACH compliant

			REVISE ONLY ON CAD SYSTEM			
			TITLE			
			Tinned Copper Battery Cable Lugs			
0			03-APL-2020		J.GAJJAR	
REV NO.	DATE	SIGN				
DIMENSIONS SHOWN IN INCH						
UNLESS OTHERWISE SPECIFIED						
TOLERLANCES $\pm 10\%$						
DRAFT WHERE APPLICABLE						
MUST REMAIN WITHIN						
DIMENSIONS						
DRWG.	MDD	CHK'D.	JMG			
BY	03-APL-2020	BY	03-APL-2020			
APP'D.	AGP	SCALE	NTS			
BY	03-APL-2020					
			PART NO. - MD0838PW		DRAWING NO.	
					MD0838PW	
					SHEET NO.	
					1 OF 1	
			FILE NAME		THIS DRAWING CONTAINS INFORMATION THAT IS	
					PROPRIETARY TO SELTERM LLC,USA AND SHOULD NOT BE	
					USED WITHOUT WRITTEN PERMISSION.	
					DIV	SIZE
						A