



NOTES:-

- 1)Made from 99.9% pure seamless copper tubes as per ASTM B188
- 2)UL 486 tested & approved
- 3)Meets SAE conductivity standards J163 and J1811
- 4)Flare barrel for easy cable entry
- 5)Electro tin plate-thickness 2 to 5 Micron
- 6)Rated for up to 600V D.C.
- 7)RoHS & REACH compliant

			REVISE ONLY ON CAD SYSTEM			
			TITLE			
			Tinned Copper Battery Cable Lugs			
0      03-APL-2020      J.GAJJAR REV NO.      DATE      SIGN					DRAWING NO.	
DIMENSIONS SHOWN IN INCH UNLESS OTHERWISE SPECIFIED TOLERLANCES ±10%  DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS					<b>MD0838PX</b>	
DRWG. MDD		CHK'D. JMG		PART NO. - MD0838PX		SHEET NO.
BY 03-APL-2020		BY 03-APL-2020				1 OF 1
APP'D. AGP		SCALE		FILE NAME		THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO SELTERM LLC,USA AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION.
BY 03-APL-2020		NTS				DIV
						SIZE
						A