



NOTES:-

- 1) Made from 99.9% pure seamless copper tubes as per ASTM B188
- 2) UL 486 tested & approved
- 3) Meets SAE conductivity standards J163 and J1811
- 4) Flare barrel for easy cable entry
- 5) Electro tin plate-thickness 2 to 5 Micron
- 6) Rated for up to 600V D.C.
- 7) RoHS & REACH compliant

			REVISE ONLY ON CAD SYSTEM			
			TITLE			
			Tinned Copper Battery Cable Lugs			
			DRAWING NO.			
			MD3012P			
			PART NO. - MD3012P		SHEET NO. 1 OF 1	
			FILE NAME		THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO SELTERM LLC, USA AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION.	
			DIV		SIZE	
					A	

REV NO.	DATE	SIGN
0	03-APL-2020	J.GAJJAR
DIMENSIONS SHOWN IN INCH		
UNLESS OTHERWISE SPECIFIED		
TOLERANCES $\pm 10\%$		
DRAFT WHERE APPLICABLE		
MUST REMAIN WITHIN		
DIMENSIONS		
DRWG.	MDD	CHK'D.
BY 03-APL-2020		JMG
APP'D.	AGP	BY 03-APL-2020
BY 03-APL-2020		SCALE
		NTS