



NOTES:-

- 1)Made from 99.9% pure seamless copper tubes as per ASTM B188
- 2)UL 486 tested & approved
- 3)Meets SAE conductivity standards J163 and J1811
- 4)Flare barrel for easy cable entry
- 5)Electro tin plate-thickness 2 to 5 Micron
- 6)Rated for up to 600V D.C.
- 7)RoHS & REACH compliant

			REVISE ONLY ON CAD SYSTEM			
			TITLE			
			Tinned Copper Battery Cable Lugs			
			DRAWING NO.			
			MD4038PXL			
			PART NO. - MD4038PXL		SHEET NO. 1 OF 1	
REV NO.    DATE    SIGN 0        03-APL-2020    J.GAJJAR			DIMENSIONS SHOWN IN INCH UNLESS OTHERWISE SPECIFIED TOLERLANCES $\pm 10\%$  DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		FILE NAME    THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO SELTERM LLC,USA AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION.    DIV    SIZE	
DRWG.    MDD    CHK'D.    JMG BY 03-APL-2020    BY 03-APL-2020 APP'D.    AGP    SCALE    NTS BY 03-APL-2020					A	