


NOTES:-

- 1)Made from 99.9% pure seamless copper tubes as per ASTM B188
- 2)UL 486 tested & approved
- 3)Meets SAE conductivity standards J163 and J1811
- 4)Flare barrel for easy cable entry
- 5)Electro tin plate-thickness 2 to 5 Micron
- 6)Rated for up to 600V D.C.
- 7)RoHS & REACH compliant

			REVISE ONLY ON CAD SYSTEM			
			TITLE			
			Tinned Copper Battery Cable Lugs			
0      03-APL-2020      J.GAJJAR REV NO.      DATE      SIGN			DIMENSIONS SHOWN IN INCH UNLESS OTHERWISE SPECIFIED TOLERLANCES ±10%		DRAWING NO.	
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS					<b>MD4038P</b>	
DRWG. MDD      CHK'D. JMG BY 03-APL-2020      BY 03-APL-2020 APP'D. AGP      SCALE BY 03-APL-2020      NTS			PART NO. - MD4038P		SHEET NO. 1 OF 1	
			FILE NAME		THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO SELTERM LLC,USA AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION.	
					DIV      SIZE	
					A	